



Product Service

# Attestation of Conformity

No. E8A 091566 0082 Rev. 00

**Holder of Attestation:** **SINENG ELECTRIC CO.,LTD.**

No.6 Hehui Road, Huishan District  
214174 Wuxi City  
PEOPLE'S REPUBLIC OF CHINA

**Name of Object:** **Converter**  
**GRID-CONNECTED HYBRID INVERTER**

This Attestation of Conformity is issued on a voluntary basis according to the Directive 2014/30/EU relating to electromagnetic compatibility. It confirms that the listed apparatus complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for conformity assessment. For details see: [www.tuvsud.com/ps-cert](http://www.tuvsud.com/ps-cert)

**Test report no.:** 4840924252600

**Date,** 2024-04-19



( Ming Gu )

Page 1 of 5

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.



Product Service

# Attestation of Conformity

No. E8A 091566 0082 Rev. 00

**Model(s):** SN5.0HT, SN6.0HT, SN8.0HT, SN10HT-X,  
SN10HT, SN12HT, SN15HT

## Description of Object:

Model	SN5.0HT	SN6.0HT	SN8.0HT	SN10HT
<b>PV input</b>				
Max. input voltage	1000 Vd.c.			
MPPT voltage range	160, ..., 950Vd.c.			
Max. input current	18/18 Ad.c.	18/18 Ad.c.	18/18 Ad.c.	18/18 Ad.c.
Isc PV (absolute maximum)	25/25 Ad.c.	25/25 Ad.c.	25/25 Ad.c.	25/25 Ad.c.
The max. number of strings per MPPT	1/1	1/1	1/1	1/1
<b>Battery input</b>				
Battery type	Li-ion			
Battery voltage range	160, ..., 600 Vd.c.			
Max. charge current	25 Ad.c.	25 Ad.c.	25 Ad.c.	25 Ad.c.
Max. discharge current	25 Ad.c.	25 Ad.c.	25 Ad.c.	25 Ad.c.
<b>AC output/input (Grid side)</b>				
Nominal voltage	3/N/PE 220/380 Va.c., 3/N/PE 230/400 Va.c.			
Nominal frequency	50 / 60 Hz			
Nominal output power	5 kW	6 kW	8 kW	10 kW
Rated apparent output power	5 kVA	6 kVA	8 kVA	10 kVA
Max. apparent output power	5.5 kVA	6.6 kVA	8.8 kVA	11 kVA
Rated output current	7.6 Aa.c.@ 220/380 Va.c. 7.3 Aa.c.@ 230/400 Va.c.	9.1 Aa.c.@ 220/380 Va.c. 8.7 Aa.c.@ 230/400 Va.c.	12.2 Aa.c.@ 220/380 Va.c. 11.6 Aa.c.@ 230/400 Va.c.	15.2 Aa.c.@ 220/380 Va.c. 14.5 Aa.c.@ 230/400 Va.c.
Max. output current	8.4 Aa.c.@ 220/380 Va.c. 8.0 Aa.c.@ 230/400 Va.c.	10.0 Aa.c.@ 220/380 Va.c. 9.6 Aa.c.@ 230/400 Va.c.	13.4 Aa.c.@ 220/380 Va.c. 12.8 Aa.c.@ 230/400 Va.c.	16.7 Aa.c.@ 220/380 Va.c. 16.0 Aa.c.@ 230/400 Va.c.
Rated(Max.) Input Power	7.5 kW	9 kW	12 kW	15 kW
Rated(Max.) Current from Grid	11.4 Aa.c.@ 220/380 Va.c.	13.7 Aa.c.@ 220/380 Va.c.	18.2 Aa.c.@ 220/380 Va.c.	22.8 Aa.c.@ 220/380 Va.c.

Page 2 of 5

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.



Product Service

# Attestation of Conformity

No. E8A 091566 0082 Rev. 00

	10.9 Aa.c.@ 230/400 Va.c.	13.1 Aa.c.@ 230/400 Va.c.	17.4 Aa.c.@ 230/400 Va.c.	21.8 Aa.c.@ 230/400 Va.c.
<b>AC output (Back-up)</b>				
Nominal voltage	3/N/PE 220/380 Va.c., 3/N/PE 230/400 Va.c.			
Nominal frequency	50 / 60 Hz			
Nominal output power	5 kW	6 kW	8 kW	10 kW
Rated(Max.) apparent output power	5 kVA	6 kVA	8 kVA	10 kVA
Rated(Max.) output current	7.6 Aa.c.@ 220/380 Va.c.	9.1 Aa.c.@ 220/380 Va.c.	12.2 Aa.c.@ 220/380 Va.c.	15.2 Aa.c.@ 220/380 Va.c.
	7.3 Aa.c.@ 230/400 Va.c.	8.7 Aa.c.@ 230/400 Va.c.	11.6 Aa.c.@ 230/400 Va.c.	14.5 Aa.c.@ 230/400 Va.c.
<b>General</b>				
Power factor range	0.8(leading), ..., 0.8(lagging)			
Protective class	I			
Ingress protection	IP 66			
Operating temperature Range	-25 °C, ..., +60 °C			
Overvoltage category	II(DC), III(AC)			
Max. operation altitude	4000 m (more than 3000m derating)			
Dimensions(W/H/D)	577*537*206 mm			
Weight	26 kg			

Model	SN10HT-X	SN12HT	SN15HT
<b>PV input</b>			
Max. input voltage	1000 Vd.c.		
MPPT voltage range	160, ..., 950Vd.c.		
Max. input current	32/18 Ad.c.	32/18 Ad.c.	32/18 Ad.c.
Isc PV (absolute maximum)	40/25 Ad.c.	40/25 Ad.c.	40/25 Ad.c.
The max. number of strings per MPPT	2/1	2/1	2/1
<b>Battery input</b>			
Battery type	Li-ion		
Battery voltage range	160, ..., 600 Vd.c.		
Max. charge current	30 Ad.c.	30 Ad.c.	30 Ad.c.
Max. discharge current	30 Ad.c.	30 Ad.c.	30 Ad.c.

Page 3 of 5

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.



Product Service

# Attestation of Conformity

No. E8A 091566 0082 Rev. 00

<b>AC output/input (Grid side)</b>			
Nominal voltage	3/N/PE 220/380 Va.c., 3/N/PE 230/400 Va.c.		
Nominal frequency	50 / 60 Hz		
Nominal output power	10 kW	12 kW	15 kW
Rated apparent output power	10 kVA	12 kVA	15 kVA
Max. apparent output power	11 kVA	13.2 kVA	16.5 kVA
Rated output current	15.2 Aa.c.@ 220/380 Va.c.	18.2 Aa.c.@ 220/380 Va.c.	22.8 Aa.c.@ 220/380 Va.c.
	14.5 Aa.c.@ 230/400 Va.c.	17.4 Aa.c.@ 230/400 Va.c.	21.8 Aa.c.@ 230/400 Va.c.
Max. output current	16.7 Aa.c.@ 220/380 Va.c.	20.0 Aa.c.@ 220/380 Va.c.	25.0 Aa.c.@ 220/380 Va.c.
	16.0 Aa.c.@ 230/400 Va.c.	19.2 Aa.c.@ 230/400 Va.c.	24.0 Aa.c.@ 230/400 Va.c.
Rated(Max.) Input Power	15 kW	18 kW	22.5 kW
Rated(Max.) Current from Grid	22.8 Aa.c.@ 220/380 Va.c.	27.3 Aa.c.@ 220/380 Va.c.	34.1 Aa.c.@ 220/380 Va.c.
	21.8 Aa.c.@ 230/400 Va.c.	26.1 Aa.c.@ 230/400 Va.c.	32.7 Aa.c.@ 230/400 Va.c.
<b>AC output (Back-up)</b>			
Nominal voltage	3/N/PE 220/380 Va.c., 3/N/PE 230/400 Va.c.		
Nominal frequency	50 / 60 Hz		
Nominal output power	10 kW	12 kW	15 kW
Rated(Max.) apparent output power	10 kVA	12 kVA	15 kVA
Rated(Max.) output current	15.2 Aa.c.@ 220/380 Va.c.	18.2 Aa.c.@ 220/380 Va.c.	22.8 Aa.c.@ 220/380 Va.c.
	14.5 Aa.c.@ 230/400 Va.c.	17.4 Aa.c.@ 230/400 Va.c.	21.8 Aa.c.@ 230/400 Va.c.
<b>General</b>			
Power factor range	0.8(leading), ..., 0.8(lagging)		
Protective class	I		
Ingress protection	IP 66		
Operating temperature Range	-25 °C, ..., +60 °C		
Overvoltage category	II(DC), III(AC)		
Max. operation altitude	4000 m (more than 3000m derating)		
Dimensions(W/H/D)	577*537*206 mm		
Weight	29 kg		

Page 4 of 5

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.



Product Service

# Attestation of Conformity

No. E8A 091566 0082 Rev. 00

**Tested  
according to:**

EN IEC 61000-6-3:2021  
EN IEC 61000-6-1:2019  
EN 62920:2017/A1:2021

Page 5 of 5

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.